

CIRRUS SYN PG

GENERAL DESCRIPTION

CIRRUS SYN PG lubricants are polyglycol-based products for use in enclosed gear, bearings, and compressors where conditions demand the unique properties of these fluids. CIRRUS SYN PG lubricants provide better wear protection, thermal and oxidation stability, and reduced sludge and deposit formation which insures enhanced performance when compared to petroleum-based lubricants. CIRRUS SYN PG lubricants are incompatible with petroleum oils. Care should be taken to make sure the two types of fluids are not mixed.

Physical Properties

CIRRUS SYN PG	220	320	460	680	1000
ISO Grade	220	320	460	680	1000
Viscosity					
@ 40°C, cSt	237	314	441	654	1000
@ 100°C, cSt	42.9	55.7	76.6	111	162.0
@ 100°F, SUS	1191	1580	2224	3312	5072
@ 210°F, SUS	206	266	366	532	774
Viscosity Index	238	245	255	268	280
Specific Gravity	1.052	1.054	1.056	1.057	1.056
Flash Point , °F (°C)	510 (266)	520 (271)	530 (277)	525 (274)	525 (274)
Pour Point, °F (°C)	-49 (-45)	-49 (-45)	-44 (-42)	-44 (-42)	-44 (-42)
FZG Gear Test	12+ Pass	12+ Pass	12+ Pass	12+ Pass	12+ Pass

NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suit ability. Product typical this publication are current as of November 24, 2010.

August 22, 2012

454 South Main Street, Wilkes-Barre, PA 18703 | P: (570) 822-1151 | F: (570) 823-1910

PRODUCT DATA SHEET